



FEATURES & SPECIFICATIONS:

Construction

- Heavy-duty cast aluminum housing and door frame
- Plated steel yoke
- Positive spring-loaded door latches
- One-piece silicone gasket forms a water-tight seal between the door frame and housing
- Aluminum cord grip at conduit entry
- Standard finish natural aluminum

Optical System

- Heat and impact resistant tempered glass lens
- Aluminum reflector

Electrical System

- Ceramic spring-loaded sockets
- Double-ended lamp supplied standard

3600 SERIES

QUARTZ
FLOODLIGHT
NON-LISTED

FOR USE IN WET
LOCATIONS

APPLICATIONS:

- Industrial yards
- Heavy equipment
- Construction sites
- Outdoor storage
- Temporary Lighting
- Security
- Signage

OPTIONS:

- 4' Pre-wired cord

SHIPPING WEIGHT:

- 6 LBS

3600 SERIES

ORDERING INFORMATION

SERIES	LAMP WATTAGE	VOLTAGE	OPTIONS
36	50	A	
SERIES 36 = 3600 SERIES	LAMP WATTAGE 30 = 300 WATT 50 = 500 WATT	VOLTAGE A = 120 VOLT 60HZ J = 240 VOLT 60HZ	OPTIONS SOC-15 = 16 / 3 50 CORD

MOUNTING OPTIONS



5029

4317

RELATED PRODUCTS



6500 SERIES
U.L. LISTED, CLASS I, DIV. 2



DISTRIBUTION
PANELS
(NON-LISTED)



2100



2200
PLUGS
(NON-LISTED)



2400

DIMENSIONS

