



### FEATURES & SPECIFICATIONS:

#### Construction

- Heavy-duty die cast aluminum housing and door frame
- Hinged door frame allows for easy maintenance
- One-piece silicone gasket forms a water-tight seal between the housing and door frame
- External hardware is corrosion resistant
- Prewired with 3' #16/3 cord (Yoke mount only)
- Available with steel yoke or 2-<sup>3</sup>/<sub>4</sub>" knuckle slipfitter painted dark bronze
- Standard finish is dark bronze powder coat

#### Optical System

- Heat and impact resistant tempered glass lens
- Anodized aluminum reflector system with wide, uniform beam pattern

#### Electrical System

- Quad-tap CWA, Class H ballasts are supplied with all pulse start metal halide fixtures and 250W & 400W high pressure sodium fixtures
- High reactance, high power factor quad-tap Class H ballast is supplied with 150W high pressure sodium
- Minimum starting temperature -40°C high pressure sodium and -30°C pulse start metal halide
- Lamp is included

### LISTINGS

- ▶ ETL tested to UL 1598
- ▶ Suitable for Wet Locations

### APPLICATIONS:

- Industrial yards
- Parking lots
- Walkways
- Facade Lighting
- Recreational areas
- Security
- Signage

# 6600 SERIES HID




## ORDERING INFORMATION


SERIES	CONSTRUCTION	WATTAGE/SOURCE	VOLTAGE	OPTIONS
<b>66</b>	<b>A</b>	<b>40P</b>	<b>MT</b>	<b>YM</b>
<b>SERIES</b> 66 = 6600 SERIES  <b>CONSTRUCTION</b> A = ALUMINUM		<b>WATTAGE/SOURCE</b> <b>PULSE START METAL HALIDE</b> 17P = 175W (ED-28) 20P = 200W (ED-28) 25P = 250W (ED-28) 32P = 320W (ED-28) 35P = 350W (ED-28) 40P = 400W (ED-28)  <b>HIGH PRESSURE SODIUM</b> 15S = 150W (ED-18) 25S = 250W (ED-18) 40S = 400W (ED-18)	<b>VOLTAGE</b> MT = MULTI-TAP BALLAST (120, 208, 240, 277V) 5T = FIVE-TAP BALLAST (120, 208, 240, 277, 480V)	<b>OPTIONS (FIELD INSTALLED)</b> PS = POLYCARBONATE SHIELD VS = VISOR WG = WIRE GUARD YM = YOKE MOUNT (STANDARD) SF = SLIPFITTER (OPTIONAL)

## MOUNTING ACCESSORIES


\*\*Mounting hardware is **not** included with fixtures and must be ordered separately.



TWO FIXTURE BULLHORN




SURFACE MOUNT ADAPTER





SLIPFITTER ADAPTER


## DIMENSIONS



YOKE MOUNT



SLIPFITTER MOUNT



SNELSON OILFIELD LIGHTING  
 8622 FAIRBANKS N HOUSTON RD  
 HOUSTON, TX 77040

[www.snelsonlights.com](http://www.snelsonlights.com)

713-937-3600 Phone  
 866-563-2832 Phone  
 713-937-3604 Fax